

Rus-Kil® Lube 60 Spray Lubricant 10-60

Petroleum Based Lubricant

PRODUCT DESCRIPTION

A hydrocarbon based lubricant containing rust inhibiting ingredients provided in a handy and efficient aerosol container. Contains no silicones.

TYPICAL USES

For industrial, commercial and residential use on thousands of items including appliances, locks, hinges, lawn and garden tools. For automotive and marine use on switches, linkages, ignitions, hinges and fittings. For sports equipments such as bicycles, motorcycles, fishing tackle and guns. For home and industrial use on power tools, office machines, relays, chains, cables and electronic instruments.

PRODUCT ADVANTAGES

Rus-Kil® Lube 60 forms a light weight film with anticorrosive and lubricating properties. Lubricates moving parts, motors, and delicate mechanisms. Protects against corrosion on metal parts of tools, machinery and sporting equipment. Penetrates to loosen rusty, frozen fasteners and stop squeaks. Displaces moisture from electrical gear and water soaked equipment.

COLORS

Amber

GLOSS

Not Applicable

PHYSICAL CONSTANTS

Recommended Film Thickness - For application in thin films for lubrication and protection. Dry film will approximate 0.1 - 0.2 mils.

APPLICATION

Method - Provided in aerosol spray with extension tube for hard to reach areas.
Thinner - Clean up overspray or excess with MoPoxOI® or mineral spirits.

SHIPPING & STORAGE

Consists of - 12 oz. Aerosol
Unit Shipping Weight - 1 lb.

Shelf Life - 12 months minimum from date of manufacture when maintained in protected storage @ 40-100°F (subject to reinspection thereafter).

APPLICATION INSTRUCTIONS

Consult your Mobile Paint Representative for the protective coating system best suited for your requirements.

Limitations: Apply in good weather when air and surface temperature are above 35°F and surface temperature is at least 5°F above the dew point. For optimum application properties, material should be between 65 to 90°F prior to mixing and application. Maintain unmixed material in closed containers in protected storage at 40 - 100°F.

The solvents contained in this product may cause lifting of previous coatings or primers to occur. Compatibility of this product over these previous coatings and any sensitive substrates should be determined by application to a test area before complete application.

Mixing: Shake can vigorously for at least one minute before application.

Application: CAREFULLY READ THE INSTRUCTIONS AND WARNINGS ON THE CAN PRIOR TO USING. Protect surrounding areas from spray mist. Press spray button firmly. Insert extension tube into spray tip for application into hard to reach areas or for limited application areas.

Cleanup: Clean all equipment and overspray immediately after use with MoPaxOI® 75-1 or mineral spirits.

Safety: Safe storage, handling and use dictate that adequate health and safety precautions be observed with this product and any recommended thinners. User is specifically directed to consult the current Material Safety Data Sheet for this product as well as precautions contained on product labeling.

Notice: The technical data contained herein are true and accurate to the best of our knowledge. All products are offered and sold subject to Mobile Paint Manufacturing Company's Standard Conditions of Sale. Published technical data and instructions are subject to change without prior notice.

10-60(10/99)

LIMITED WARRANTY

The successful performance of this product is highly dependent on many factors beyond our control. Results are highly dependent upon the skill of the operator. This product is manufactured to meet the highest level of consistency and quality for the intended use. Mobile Paint warrants that its products meet the specifications which it sets for them. Should this product be proven to be off-specification within one year from date of shipment, Mobile Paint will, at its sole discretion, either replace the product or issue credit for the original purchase price of the product. The replacement or refund shall be the buyer's sole remedy and Mobile Paint and its affiliates **MAKE NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, DESIGN COMPATIBILITY AND FITNESS FOR A PARTICULAR PURPOSE. LABOR OR COST OF LABOR AND OTHER INCIDENTAL AND/OR CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED.** The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.