



PRODUCT DATA

FLAT LATEX PAINT
Black 23-DX-3

Vinyl Acrylic Emulsion

PRODUCT DESCRIPTION	A durable, quality flat latex finish. Lead, mercury and chromate free.	
TYPICAL USES	For industrial and commercial use as a flat finish on properly prepared plaster, wallboard, wood, canvas, masonry or other surfaces.	
PRODUCT ADVANTAGES	Flat Latex Paint provides a durable, economical, and attractive finish. Easy to apply, fast drying, low odor and water thinned. Lead, mercury and chromate free. Low VOC.	
COLORS	Black. Special colors available subject to minimum order.	
GLOSS	Flat	
PHYSICAL CONSTANTS	Nonvolatile -	By weight - 37.3 ± 2.0% By volume - 24.5 ± 1.0%
	VOC (Calculated) -	1.33 lbs./gal. 159 grams/liter
	Flash Point -	>250°F (Setaflash)
	Weight per gallon -	10.0 ± 0.2 lbs.
APPLICATION	Recommended Film Thickness - 1.0 mils dry, 4.1 mils wet Theoretical Coverage @ 1.0 mils dry - 394 sq. ft./gal. Method - Brush, roller, conventional or airless spray Thinner - water	
	Dry time @ 75°F -	To touch - 30 minutes To handle - 1 hour To recoat - 4 hours
SHIPPING & STORAGE	Consists of -	1 Gallon Unit 5 Gallon Unit
	Unit Shipping Weight	11 lbs. 53 lbs.
	Shelf Life - 12 months minimum from date of manufacture when maintained in protected storage @ 40-100°F (subject to reinspection thereafter).	

23DX3 (11/95)