

Mobile Paint Mfg. Co., Inc.

SAFETY DATA SHEET

OSHA HCS (29 CFR 1910-1200)

SECTION 1 - PRODUCT AND MANUFACTURER IDENTIFICATION

Product Name: BOUNDARY LINE PAINT - WHITE Product Code: 57-16

Mobile Paint Mfg. Co., Inc.
P.O. Box 717
4775 Hamilton Blvd.
Theodore, AL 36582

Emergency Phone: Chemtel, Inc
1-800-255-3924
+1-813-248-0585
(Chemtel 24 Hour Emergency Number)

Information Phone: 251-443-6110

Product Use: Paint

Not recommended for: Contact Manufacturer

SECTION 2 - HAZARD DATA

GHS Ratings:

Flammable liquid	2	Flash point < 23°C and initial boiling point > 35°C (95°F)
Skin corrosive	2	Reversible adverse effects in dermal tissue, Draize score: >= 2.3 < 4.0 or persistent inflammation
Eye corrosive	2A	Eye irritant: Subcategory 2A, Reversible in 21 days
Carcinogen	1A	Known Human Carcinogen Based on human evidence
Aspiration hazard	1	Aspiration Toxicity Category 1: Known (regarded)- human evidence - hydrocarbons with kinematic viscosity ? 20.5 mm ² /s at 40° C.

GHS Hazards

H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H350	May cause cancer

GHS Precautions

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat/sparks/open flames/hot surfaces – No smoking
P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P264	Wash hands and skin thoroughly after handling
P280	Wear protective gloves/protective clothing/eye protection/face protection
P281	Use personal protective equipment as required
P321	Specific treatment (see information on this label)
P331	Do NOT induce vomiting
P362	Take off contaminated clothing and wash before reuse
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P302+P352	IF ON SKIN: Wash with soap and water

P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
P308+P313	IF exposed or concerned: Get medical advice/attention
P332+P313	If skin irritation occurs: Get medical advice/attention
P337+P313	Get medical advice/attention
P370+P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction
P405	Store locked up
P403+P235	Store in a well ventilated place. Keep cool
P501	Dispose of contents/container in accordance with all local, regional, national and international regulations.

Signal Word: Danger



SECTION 3 - COMPOSITION / HAZARDOUS INGREDIENTS

Chemical Name	CAS number	Weight Concentration %
ethyl benzene	100-41-4	0.16%
calcium carbonate	1317-65-3	30.00% - 40.00%
titanium dioxide	13463-67-7	5.00% - 10.00%
magnesium silicate	14807-96-6	10.00% - 20.00%
crystalline silica (quartz)	14808-60-7	0.29%
aliphatic naphtha, light, hydrotreated	64742-49-0	1.00% - 5.00%
aliphatic naphtha (VM&P)	64742-89-8	10.00% - 20.00%
aliphatic petroleum distillates, light, hydrotreated	68410-97-9	1.00% - 5.00%
mineral spirits	8052-41-3	1.00% - 5.00%

SECTION 4 - FIRST AID MEASURES

Inhalation: Remove to fresh air. Administer oxygen if breathing is difficult. Restore breathing if necessary and call a physician immediately. Treat symptomatically.

Eyes: Remove contact lenses if worn. Flush immediately with large amounts of water for at least 15 minutes. If symptoms persist, consult with a doctor for medical treatment.

Skin: Wash affected areas with soap and water. Remove and launder contaminated clothing. Consult a doctor if skin irritation continues.

Ingestion: Do not induce vomiting. Rinse out mouth and drink plenty of water to dilute. Never give anything by mouth to an unconscious person. Get medical help immediately.

Most important symptoms and effects, both acute and delayed

Symptoms: No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians: Treat symptomatically

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point: 14 C (57 F)

LEL: 1.00

UEL: 8.00

Extinguishing media**Suitable extinguishing agents:**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. CO₂, extinguishing powder or water spray may be effective.

For safety reasons unsuitable extinguishing agents: **CAUTION!** Use of water spray may be inefficient.

Unusual Fire and Explosion Hazards

Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers.

Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Advice for firefighters

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention. Keep containers tightly closed. Isolate from heat, sparks, and open flame.

Protective equipment:

Full protective equipment including self-contained breathing apparatus should be used.

SECTION 6 - ACCIDENTAL RELEASE MEASURES
--

Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol. Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation. Keep away from ignition sources. Protect from heat.

Environmental precautions: Do not allow to enter sewers/ surface or ground water. See Section 12 for additional ecological information.

Methods and material for containment and cleaning up:

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders). Dispose contaminated material as waste according to item 13. Do not flush with water or aqueous cleansing agents. Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7 - HANDLING AND STORAGE

Handling Precautions:**Precautions for safe handling**

Prevent formation of fine mist and vapor buildup during and after use. Avoid splashes or spray in enclosed areas. Use only in well ventilated areas. Do not get in eyes. Avoid skin contact. Can cause allergic respiratory reaction. Can cause allergic skin reaction. Prevent prolonged or repeated breathing of vapors or spray mist. Avoid breathing of sanding dust. Wash contaminated clothing thoroughly. Wash skin thoroughly with soap and water after handling. Close container after each use. Do not transfer this product to unlabeled containers. Do not handle until the manufacturer's safety precautions have been read and understood. Keep out of reach of children.

Information about protection against explosions and fires:

Keep ignition sources away. Do not smoke. Protect against electrostatic discharges.

Storage Requirements:

Do not store above 120 F. Store large quantities only in buildings designed to comply with OSHA 1910.106. Keep closures tight and container upright to prevent leakage. Do not store or use near heat, sparks or flame. Never use pressure to empty. Drum must not be washed out or used for other purposes. Drums of this material should be grounded when pouring.

Regulatory Requirements:

Consult NFPA Code. Use approved bonding and grounding procedures.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION
--

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
-------------------------	----------------------	-----------------------	-----------------------

ethyl benzene 100-41-4	TLV-TWA 100ppm PEL-TWA 100ppm STEL 125 ppm	TWA 20ppm	NIOSH REL TWA 100ppm NIOSH REL ST 125ppm
calcium carbonate 1317-65-3	15 mg/m3 PEL	2 mg/m3 TLV	Not Established
titanium dioxide 13463-67-7	PEL 15 mg/cu.m. 8 hours Form: Total dust	TLV 10 mg/cu.m. 8 hours	Not Established
magnesium silicate 14807-96-6	PEL 15 mg/m3 inhalable dust	Not Established	Not Established
crystalline silica (quartz) 14808-60-7	PEL 0.1 mg/m3 TWA 0.1 mg/m3	TWA 0.025 mg/m3	Not Established
aliphatic naphtha, light, hydrotreated 64742-49-0	Not Established	Not Established	Not Established
aliphatic naphtha (VM&P) 64742-89-8	Not Established	Not Established	Not Established
aliphatic petroleum distillates, light, hydrotreated 68410-97-9	Not Established	Not Established	Not Established
mineral spirits 8052-41-3	OSHA Z-1 500 ppm - TWA OSHA Z-1 1000 mg/m3 - TWA	ACGIH TLV 200 mg/m3 - TWA	Not Established

Engineering Controls:

Appropriate engineering controls include ventilations systems, eyewash stations and emergency showers.

Ventilation:

All application areas should be ventilated in accordance to OSHA regulation 29 CFR 1910.94, 1910.107, 1910.108. Remove decomposition products formed during welding or flame cutting on surface coated with this product. If baking, vent fumes.

Work / Hygienic Practices:

Wash skin thoroughly before breaks and meals and at the end of work period .

Respiratory Protection:

Use a NIOSH-approved respirator to prevent overexposure, when exposure exceeds occupational exposure limits (Section 8). Use either an atmosphere-supplying respirator or an air-purifying respirator for organic vapors in compliance with 29 CFR 1910.134, with provision for mist removal if conditions so indicate. If isocyanate compounds are present in spray applications or other situations which may produce inhalation exposures, use a respirator that is recommended or approved for use in isocyanate-containing environments.

Eye Protection:

Safety eyewear including splashguards or side shields recommended.

Protective Gloves:

Recommended. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Other Protective Clothing or Equipment:

Use protective outerwear and prevent prolonged skin contact with contaminated clothing.

Contaminated Equipment:

Thoroughly clean all contaminated clothing and personal protection equipment.

SECTION 9 - PHYSICAL / CHEMICAL CHARACTERISTICS

Information on basic physical and chemical properties

<p>Appearance: Liquid</p> <p>Vapor Pressure: 10.2 mmHg @ 25C</p> <p>Vapor Density: 4.3</p> <p>Specific Gravity: 1.54</p>	<p>Odor: Typical solvent paint odor</p> <p>Odor threshold: No information available</p> <p>pH: No information available</p> <p>Melting point: No information available</p>
--	--

<p>Freezing point: No information available</p> <p>Boiling range: 90°C</p> <p>Evaporation rate: slower than ether</p> <p>Partition coefficient (n- no data octanol/water):</p> <p>Viscosity: No information available</p> <p>VOC - water/exempt (lb/gal) 2.70</p> <p>VOC emitted (lb/gal) 2.70</p>	<p>Solubility: No information available</p> <p>Flash point: 57 F, 14 C</p> <p>Flammability: No information available</p> <p>Decomposition temperature: No information available</p> <p>VOC - water/exempt (g/L) 324</p> <p>VOC emitted (g/L) 324</p>
---	--

SECTION 10 - STABILITY AND REACTIVITY

Reactivity - No data available

Chemical stability - Stable under recommended storage conditions.
STABLE

Possibility of Hazardous Reactions - None under normal conditions of use.

Conditions to Avoid - Heat, sparks, open flame, static electricity, sources of ignition, elevated temperatures .

Incompatible Materials - Strong acids and alkali, strong oxidizing agents.

Incompatibility of Individual Components:
No information available

Hazardous decomposition products - Carbon monoxide and carbon dioxide

Information for Individual Components:
No information available
Hazardous polymerization will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Mixture Toxicity
Inhalation Toxicity LC50: 68mg/L

Component Toxicity

100-41-4	ethyl benzene	Oral LD50: 3,500 mg/kg (rat) Inhalation LC50: 4,000 ppm (rat)
64742-49-0	aliphatic naphtha, light, hydrotreated	Dermal LD50: 2,001 mg/kg (rabbit)
64742-89-8	aliphatic naphtha (VM&P)	Dermal LD50: 2,001 mg/kg (rabbit)
68410-97-9	aliphatic petroleum distillates, light, hydrotreated	Dermal LD50: 2,001 mg/kg (rabbit)
8052-41-3	mineral spirits	Oral LD50: 5,000 mg/kg (rat) Dermal LD50: 2,000 mg/kg (rabbit)

CHRONIC HEALTH HAZARDS:
Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Routes of Entry:

Inhalation	Skin Contact	Eye Contact	Ingestion
-------------------	---------------------	--------------------	------------------

Target Organs:

Eyes	Lungs	Central Nervous System	Skin
-------------	--------------	-------------------------------	-------------

Effects of Overexposure

Eye contact: Eye contact can cause severe irritation, redness, tearing, blurred vision. May be a sensitizer in some individuals.

Skin contact: Skin contact can cause moderate irritation, defatting, dermatitis. May be a sensitizer in some individuals.

Inhalation: Anesthetic, excessive inhalation can cause irritation of the respiratory tract, or acute nervous system depression characterized by headache, dizziness, staggering gait, confusion, unconsciousness, coma and even asphyxiation.

Ingestion: Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury and possibly even death.

Sensitization: No data available.

Mutagenicity: No data available.

Reproductive Toxicity: No data available.

Teratogenicity: No data available.

Specific Target Organ Toxicity - Single Exposure: No data available.

Specific Target Organ Toxicity - Repeated Exposure: No data available.

Carcinogenicity:

For Mixture - No information available

For Components - The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing) .

NOTE: Reference to **Crystalline Silica** and/or **Quartz** is based on exposure to unbound respirable particles and is not generally applicable to this product as supplied.

NOTE: Reference to **ethyl benzene** refers to IARC classification of ethyl benzene as possibly carcinogenic to humans (Group 2B) based on sufficient evidence in experimental animals but there is inadequate evidence that ethyl benzene causes cancer in humans.

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
14808-60-7	crystalline silica (quartz)	0.29	crystalline silica (quartz): IARC working group classified as carcinogenic to humans (Group 1). NTP - Group 2A ACGIH - A2 suspected human carcinogen OSHA - listed
100-41-4	ethyl benzene	0.16	ethyl benzene: IARC: Group 2B - Possibly carcinogenic to humans ACGIH: Confirmed animal carcinogen with unknown relevance to humans OSHA: Not identified as a carcinogen or possible carcinogen NTP: Not identified as a known or anticipated carcinogen

SECTION 12 - ECOLOGICAL INFORMATION

Persistence and degradability - No information available.

Bioaccumulative potential - No information available.

Mobility in soil - No information available.

Ecotoxicological effects - No information available.

Other adverse effects - No information available.

Additional ecological information:

General notes:

Do not allow product to reach ground water, water course or sewage system . Danger to drinking water if even small quantities leak into the ground.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Component Ecotoxicity

mineral spirits

96 hr LC50 Oncorhynchus mykiss: 25 mg/l; 48 hr EL50 Daphnia magna: 1.4 mg/l; 72 hr EL50 Pseudokirchneriella subcapitata: 1 mg/l

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste disposal methods:

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Residual materials should be treated as hazardous unless proven to be otherwise.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

Empty Container Warning:

Emptied containers may contain product residue. Follow label warnings even after container is emptied. Residual vapors may explode on ignition. Do not reuse container.

SECTION 14 - TRANSPORT INFORMATION

Shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transportation does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment and compliance with applicable regulations is the sole responsibility of the person offering the product for transport.

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	Paint	1263	II	3

SECTION 15 - REGULATORY INFORMATION

Safety, health and environmental regulations specific for the substance/mixture.

California Proposition 65

This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

- 100-41-4 ethyl benzene
- 14808-60-7 crystalline silica (quartz)
- 13463-67-7 titanium dioxide

CERCLA

This material, as supplied, contains the following chemicals regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) - 40 CFR 302

- 100-41-4 ethyl benzene

Hazardous Air Pollutants (HAPs) Content

Hazardous Air Pollutants subject to the provisions of the Clean Air Act, Title I Section 112 'National Emission Standards for Hazardous Air Pollutants'

- 100-41-4 ethyl benzene 0.2 %

Massachusetts RTK:

- ethyl benzene 100-41-4
- crystalline silica (quartz) 14808-60-7

New Jersey RTK:

- ethyl benzene 100-41-4
- crystalline silica (quartz) 14808-60-7
- mineral spirits 8052-41-3
- aliphatic naphtha (VM&P) 64742-89-8

Pennsylvania RTK:

- ethyl benzene 100-41-4
- crystalline silica (quartz) 14808-60-7

mineral spirits 8052-41-3
titanium dioxide 13463-67-7
aliphatic naphtha (VM&P) 64742-89-8

Rhode Island Hazardous Substance List:

ethyl benzene 100-41-4
crystalline silica (quartz) 14808-60-7

SARA 313

This product contains a chemical or chemicals which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA 313).
100-41-4 ethyl benzene 0.2 %

TSCA

All chemicals in this product are listed, or are exempt from listing, on the TSCA inventory unless they are listed here:

SECTION 16 - OTHER INFORMATION

Hazardous Material Information System (HMIS)

HEALTH	<input type="text" value="2"/>	HMIS & NFPA Hazard Rating Legend * = Chronic Health Hazard 0 = INSIGNIFICANT 1 = SLIGHT 2 = MODERATE 3 = HIGH
FLAMMABILITY	<input type="text" value="3"/>	
PHYSICAL HAZARD	<input type="text" value="0"/>	
PERSONAL PROTECTION	<input type="text"/>	

DISCLAIMER: The information provided in this MSDS has been obtained from sources believed to be accurate and reliable. It is furnished without warranty of any kind, express or implied. Recipients should determine that the information is current and suitable for the protection of the environment and the health and safety of your employees and users of this product.

Date revised: 2015-10-27
Date Prepared: 10/27/2015

Reviewer Revision 1