

Mobile Paint Mfg. Co., Inc.

SAFETY DATA SHEET

OSHA HCS (29 CFR 1910-1200)

SECTION 1 - PRODUCT AND MANUFACTURER IDENTIFICATION

Product Name: ACRYLIC ENAMEL - SAFETY YELLOW #2 Product Code: 58-AN-17

Mobile Paint Mfg. Co., Inc.
P.O. Box 717
4775 Hamilton Blvd.
Theodore, AL 36582

Emergency Phone: Chemtel, Inc
1-800-255-3924
+1-813-248-0585
(Chemtel 24 Hour Emergency Number)

Information Phone: 251-443-6110
FAX: 251-408-0410

Product Use: Paint
Not recommended for: Contact Manufacturer

SECTION 2 - HAZARD DATA

GHS Ratings:

| | | |
|-------------------|----|---|
| Flammable liquid | 3 | Flash point $\geq 23^{\circ}\text{C}$ and $\leq 60^{\circ}\text{C}$ (140°F) |
| Skin corrosive | 2 | Reversible adverse effects in dermal tissue, Draize score: $\geq 2.3 < 4.0$ or persistent inflammation |
| Eye corrosive | 2A | Eye irritant: Subcategory 2A, Reversible in 21 days |
| Carcinogen | 2 | Limited evidence of human or animal carcinogenicity |
| Aspiration hazard | 1 | Aspiration Toxicity Category 1: Known (regarded)- human evidence - hydrocarbons with kinematic viscosity ≥ 20.5 mm ² /s at 40°C . |

GHS Hazards

| | |
|------|--|
| H226 | Flammable liquid and vapour |
| H304 | May be fatal if swallowed and enters airways |
| H315 | Causes skin irritation |
| H319 | Causes serious eye irritation |
| H351 | Suspected of causing cancer |

GHS Precautions

| | |
|-----------|---|
| P201 | Obtain special instructions before use |
| P202 | Do not handle until all safety precautions have been read and understood |
| P210 | Keep away from heat/sparks/open flames/hot surfaces – No smoking |
| P233 | Keep container tightly closed |
| P240 | Ground/bond container and receiving equipment |
| P241 | Use explosion-proof electrical/ ventilating/ lighting/ equipment |
| P242 | Use only non-sparking tools |
| P243 | Take precautionary measures against static discharge |
| P264 | Wash hands and skin thoroughly after handling |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection |
| P281 | Use personal protective equipment as required |
| P321 | Specific treatment (see information on this label) |
| P331 | Do NOT induce vomiting |
| P362 | Take off contaminated clothing and wash before reuse |
| P301+P310 | IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician |
| P302+P352 | IF ON SKIN: Wash with soap and water |

| | |
|----------------|---|
| P303+P361+P353 | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower |
| P305+P351+P338 | IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing |
| P308+P313 | IF exposed or concerned: Get medical advice/attention |
| P332+P313 | If skin irritation occurs: Get medical advice/attention |
| P337+P313 | Get medical advice/attention |
| P370+P378 | In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction |
| P405 | Store locked up |
| P403+P235 | Store in a well ventilated place. Keep cool |
| P501 | Dispose of contents/container in accordance with all local, regional, national and international regulations. |

Signal Word: Danger



SECTION 3 - COMPOSITION / HAZARDOUS INGREDIENTS

| Chemical Name | CAS number | Weight Concentration % |
|----------------------------------|------------|------------------------|
| ethyl benzene | 100-41-4 | 3.50% |
| styrene | 100-42-5 | 0.57% |
| ethylene glycol monobutyl ether | 111-76-2 | 2.30% |
| xylene, mixed isomers | 1330-20-7 | 20.00% |
| titanium dioxide | 13463-67-7 | 5.00% - 10.00% |
| alkanes, C20-28, chloro | 63449-39-8 | 1.00% - 5.00% |
| aliphatic naphtha (VM&P) | 64742-89-8 | 1.00% - 5.00% |
| aromatic light petroleum solvent | 64742-95-6 | 10.00% - 20.00% |
| 1,2,4-trimethylbenzene | 95-63-6 | 7.80% |
| cumene | 98-82-8 | 1.30% |

SECTION 4 - FIRST AID MEASURES

Inhalation: Remove to fresh air. Administer oxygen if breathing is difficult. Restore breathing if necessary and call a physician immediately. Treat symptomatically.

Eyes: Remove contact lenses if worn. Flush immediately with large amounts of water for at least 15 minutes. If symptoms persist, consult with a doctor for medical treatment.

Skin: Wash affected areas with soap and water. Remove and launder contaminated clothing. Consult a doctor if skin irritation continues.

Ingestion: Do not induce vomiting. Rinse out mouth and drink plenty of water to dilute. Never give anything by mouth to an unconscious person. Get medical help immediately.

Most important symptoms and effects, both acute and delayed

Symptoms: No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians: Treat symptomatically

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point: 28 C (82 F)

LEL: 1.00

UEL: 11.00

Extinguishing media

Suitable extinguishing agents:

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. CO₂, extinguishing powder or water spray may be effective.

For safety reasons unsuitable extinguishing agents: **CAUTION!** Use of water spray may be inefficient.

Unusual Fire and Explosion Hazards

Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers.

Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Advice for firefighters

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention. Keep containers tightly closed. Isolate from heat, sparks, and open flame.

Protective equipment:

Full protective equipment including self-contained breathing apparatus should be used.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol. Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation. Keep away from ignition sources. Protect from heat.

Environmental precautions: Do not allow to enter sewers/ surface or ground water. See Section 12 for additional ecological information.

Methods and material for containment and cleaning up:

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders). Dispose contaminated material as waste according to item 13. Do not flush with water or aqueous cleansing agents. Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7 - HANDLING AND STORAGE

Handling Precautions:

Precautions for safe handling

Prevent formation of fine mist and vapor buildup during and after use. Avoid splashes or spray in enclosed areas. Use only in well ventilated areas. Do not get in eyes. Avoid skin contact. Can cause allergic respiratory reaction. Can cause allergic skin reaction. Prevent prolonged or repeated breathing of vapors or spray mist. Avoid breathing of sanding dust. Wash contaminated clothing thoroughly. Wash skin thoroughly with soap and water after handling. Close container after each use. Do not transfer this product to unlabeled containers. Do not handle until the manufacturer's safety precautions have been read and understood. Keep out of reach of children.

Information about protection against explosions and fires:

Keep ignition sources away. Do not smoke. Protect against electrostatic discharges.

Storage Requirements:

Do not store above 120 F. Store large quantities only in buildings designed to comply with OSHA 1910.106. Keep closures tight and container upright to prevent leakage. Do not store or use near heat, sparks or flame. Never use pressure to empty. Drum must not be washed out or used for other purposes. Drums of this material should be

grounded when pouring.

Regulatory Requirements:

Consult NFPA Code. Use approved bonding and grounding procedures.

| SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION | | | |
|---|--|---|--|
| Chemical Name / CAS No. | OSHA Exposure Limits | ACGIH Exposure Limits | Other Exposure Limits |
| ethyl benzene 100-41-4 | TLV-TWA 100ppm PEL-TWA 100ppm STEL 125 ppm | TWA 20ppm | NIOSH REL TWA 100ppm NIOSH REL ST 125ppm |
| styrene 100-42-5 | STEL 75ppm | Not Established | Not Established |
| ethylene glycol monobutyl ether 111-76-2 | PEL: 50 ppm | 20 ppm TWA 5 ppm Recommended exposure limit | Not Established |
| xylene, mixed isomers 1330-20-7 | PEL 100 ppm | TLV 100 ppm | TWA 435 mg/cu.m. |
| titanium dioxide 13463-67-7 | PEL 15 mg/cu.m. 8 hours Form: Total dust | TLV 10 mg/cu.m. 8 hours | Not Established |
| alkanes, C20-28, chloro 63449-39-8 | Not Established | Not Established | Not Established |
| aliphatic naphtha (VM&P) 64742-89-8 | Not Established | Not Established | Not Established |
| aromatic light petroleum solvent 64742-95-6 | TWA 500 ppm 2000 mg/m3 | TWA 200 mg/m3 (as total hydrocarbon vapor) | Not Established |
| 1,2,4-trimethylbenzene 95-63-6 | TLV-TWA 25ppm STEL 35ppm | Not Established | Not Established |
| cumene 98-82-8 | TWA 50 ppm | TWA 50 ppm | Not Established |

Engineering Controls:

Appropriate engineering controls include ventilations systems, eyewash stations and emergency showers.

Ventilation:

All application areas should be ventilated in accordance to OSHA regulation 29 CFR 1910.94, 1910.107, 1910.108. Remove decomposition products formed during welding or flame cutting on surface coated with this product. If baking, vent fumes.

Work / Hygienic Practices:

Wash skin thoroughly before breaks and meals and at the end of work period .

Respiratory Protection:

Use a NIOSH-approved respirator to prevent overexposure, when exposure exceeds occupational exposure limits (Section 8). Use either an atmosphere-supplying respirator or an air-purifying respirator for organic vapors in compliance with 29 CFR 1910.134, with provision for mist removal if conditions so indicate. If isocyanate compounds are present in spray applications or other situations which may produce inhalation exposures, use a respirator that is recommended or approved for use in isocyanate-containing environments.

Eye Protection:

Safety eyewear including splashguards or side shields recommended.

Protective Gloves:

Recommended. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material should be based on consideration of the penetration times, rates of diffusion and the degradation.

Other Protective Clothing or Equipment:

Use protective outerwear and prevent prolonged skin contact with contaminated clothing.

Contaminated Equipment:

Thoroughly clean all contaminated clothing and personal protection equipment.

SECTION 9 - PHYSICAL / CHEMICAL CHARACTERISTICS

Information on basic physical and chemical properties

| | |
|--|---|
| Appearance: Liquid | Odor: Typical solvent paint odor |
| Vapor Pressure: 6.1 mm Hg @ 20 C | Odor threshold: No information available |
| Vapor Density: 3.7 | pH: No information available |
| Specific Gravity: 1.00 | Melting point: No information available |
| Freezing point: No information available | Solubility: No information available |
| Boiling range: 90°C | Flash point: 82 F, 28 C |
| Evaporation rate: slower than ether | Flammability: No information available |
| Partition coefficient (n- no data octanol/water): | Autoignition temperature: N/A |
| Decomposition temperature: No information available | Viscosity: No information available |
| VOC - water/exempt (g/L) 529 | VOC - water/exempt (lb/gal) 4.41 |
| VOC emitted (g/L) 529 | VOC emitted (lb/gal) 4.41 |

SECTION 10 - STABILITY AND REACTIVITY

Reactivity - No data available

Chemical stability - Stable under recommended storage conditions.

STABLE

Possibility of Hazardous Reactions - None under normal conditions of use.

Conditions to Avoid - Heat, sparks, open flame, static electricity, sources of ignition, elevated temperatures.

Incompatible Materials - Strong acids and alkali, strong oxidizing agents.

Incompatibility of Individual Components:

No information available

Hazardous decomposition products - Carbon monoxide and carbon dioxide

Information for Individual Components:

No information available

Hazardous polymerization will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Mixture Toxicity

Dermal Toxicity LD50: 3,469mg/kg

Inhalation Toxicity LC50: 100mg/L

Component Toxicity

100-41-4

ethyl benzene

Oral LD50: 3,500 mg/kg (rat) Inhalation LC50: 4,000 ppm (rat)

111-76-2

ethylene glycol monobutyl ether

Oral LD50: 745 mg/kg (Rat) Dermal LD50: 1,250 mg/kg (Rat) Inhalation LC50: 550 ppm (Rat)

1330-20-7

xylene, mixed isomers

Oral LD50: 3,523 mg/kg (Rat, male) Dermal LD50: 1,100 mg/kg (Rabbit)

64742-89-8

aliphatic naphtha (VM&P)

Dermal LD50: 2,001 mg/kg (rabbit)

64742-95-6

aromatic light petroleum solvent

Oral LD50: 5,000 mg/kg (rat) Dermal LD50: 2,000 mg/kg (rabbit)

CHRONIC HEALTH HAZARDS:

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Routes of Entry:

| | | | |
|------------|--------------|-------------|-----------|
| Inhalation | Skin Contact | Eye Contact | Ingestion |
|------------|--------------|-------------|-----------|

Target Organs:

| | | | | |
|------|---------|-------|------------------------|------|
| Eyes | Kidneys | Lungs | Central Nervous System | Skin |
|------|---------|-------|------------------------|------|

Effects of Overexposure

Eye contact: Eye contact can cause severe irritation, redness, tearing, blurred vision. May be a sensitizer in some individuals. Eye contact can cause mild irritation, redness, tearing, blurred vision. May be a sensitizer in individuals with unusual allergic sensitivity.

Skin contact: Skin contact can cause moderate irritation, defatting, dermatitis. May be a sensitizer in some individuals. Skin contact can cause mild irritation, defatting, dermatitis. May be a sensitizer in individuals with unusual allergic sensitivity.

Inhalation: Anesthetic, excessive inhalation can cause irritation of the respiratory tract, or acute nervous system depression characterized by headache, dizziness, staggering gait, confusion, unconsciousness, coma and even asphyxiation. Excessive inhalation can cause irritation of the respiratory tract. Headache, slight dizziness and nausea possible in individuals with unusual allergic sensitivity.

Ingestion: Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury and possibly even death. Ingestion can cause gastrointestinal irritation and nausea.

Sensitization: No data available.

Mutagenicity: No data available.

Reproductive Toxicity: No data available.

Teratogenicity: No data available.

Specific Target Organ Toxicity - Single Exposure: No data available.

Specific Target Organ Toxicity - Repeated Exposure: No data available.

Carcinogenicity:**For Mixture** - No information available**For Components** - The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).**Note:** Reference to **ethyl benzene** refers to IARC classification of ethyl benzene as possibly carcinogenic to humans (Group 2B) based on sufficient evidence in experimental animals but there is inadequate evidence that ethyl benzene causes cancer in humans.

| <u>CAS Number</u> | <u>Description</u> | <u>% Weight</u> | <u>Carcinogen Rating</u> |
|-------------------|--------------------|-----------------|---|
| 100-41-4 | ethyl benzene | 3.5 | ethyl benzene: IARC: Group 2B - Possibly carcinogenic to humans ACGIH: Confirmed animal carcinogen with unknown relevance to humans OSHA: Not identified as a carcinogen or possible carcinogen NTP: Not identified as a known or anticipated carcinogen |

SECTION 12 - ECOLOGICAL INFORMATION

Persistence and degradability - No information available.

Bioaccumulative potential - No information available.

Mobility in soil - No information available.

Ecotoxicological effects - No information available.

Other adverse effects - No information available.

Additional ecological information:

General notes:

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Component Ecotoxicity

| | |
|----------------------------------|--|
| ethylene glycol monobutyl ether | 96 Hr. LC50 (Oncorhynchus mykiss (rainbow trout)) 1,474 mg/l (static); 48 Hr. EC50 (Daphnia magna (Water flea)) 1,800 mg/l (static); 72 Hr EC50 (Pseudokirchneriella subcapitata (green algae)) 911 mg/l (static); |
| xylene, mixed isomers | 96 Hr LC50 Pimephales promelas: 13.4 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 2.661 - 4.093 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 13.5 - 17.3 mg/L; 96 Hr LC50 Lepomis macrochirus: 13.1 - 16.5 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 19 mg/L; 96 Hr LC50 Lepomis macrochirus: 7.711 - 9.591 mg/L [static]; 96 Hr LC50 Pimephales promelas: 23.53 - 29.97 mg/L [static]; 96 Hr LC50 Cyprinus carpio: 780 mg/L [semi-static]; 96 Hr LC50 Cyprinus carpio: >780 mg/L; 96 Hr LC50 Poecilia reticulata: 30.26 - 40.75 mg/L [static] 48 Hr EC50 water flea: 3.82 mg/L; 48 Hr LC50 Gammarus lacustris: 0.6 mg/L |
| aromatic light petroleum solvent | 96 hr LL50 Oncorhynchus mykiss: 10 mg/l; 48 hr EL50 Daphnia magna: 4.5 mg/l; 72 hr EL50 Pseudokirchneriella subcapitata: 3.1 mg/l |

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste disposal methods:

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Residual materials should be treated as hazardous unless proven to be otherwise.

Notice to user:

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

Empty Container Warning:

Emptied containers may contain product residue. Follow label warnings even after container is emptied. Residual vapors may explode on ignition. Do not reuse container.

SECTION 14 - TRANSPORT INFORMATION

Shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transportation does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment and compliance with

applicable regulations is the sole responsibility of the person offering the product for transport .

| <u>Agency</u> | <u>Proper Shipping Name</u> | <u>UN Number</u> | <u>Packing Group</u> | <u>Hazard Class</u> |
|---------------|-----------------------------|------------------|----------------------|---------------------|
| DOT | Paint | 1263 | III | 3 |

SECTION 15 - REGULATORY INFORMATION

California Proposition 65

This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

100-42-5 styrene
98-82-8 cumene
100-41-4 ethyl benzene
13463-67-7 titanium dioxide

CERCLA

This material, as supplied, contains the following chemicals regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) - 40 CFR 302

111-76-2 ethylene glycol monobutyl ether
100-41-4 ethyl benzene
1330-20-7 xylene, mixed isomers

Florida Hazardous Substance List :

ethyl benzene 100-41-4

Hazardous Air Pollutants (HAPs) Content

Hazardous Air Pollutants subject to the provisions of the Clean Air Act, Title I Section 112 'National Emission Standards for Hazardous Air Pollutants'

100-42-5 styrene 0.6 %
98-82-8 cumene 1.3 %
100-41-4 ethyl benzene 3.5 %
1330-20-7 xylene, mixed isomers 20.0 %

Massachusetts RTK:

cumene 98-82-8
ethylene glycol monobutyl ether 111-76-2
ethyl benzene 100-41-4
1,2,4-trimethylbenzene 95-63-6
xylene, mixed isomers 1330-20-7

New Jersey RTK:

cumene 98-82-8
ethylene glycol monobutyl ether 111-76-2
ethyl benzene 100-41-4
aliphatic naphtha (VM&P) 64742-89-8
1,2,4-trimethylbenzene 95-63-6
aromatic light petroleum solvent 64742-95-6
xylene, mixed isomers 1330-20-7

Pennsylvania RTK:

cumene 98-82-8
ethylene glycol monobutyl ether 111-76-2
ethyl benzene 100-41-4
aliphatic naphtha (VM&P) 64742-89-8
titanium dioxide 13463-67-7
1,2,4-trimethylbenzene 95-63-6
aromatic light petroleum solvent 64742-95-6
xylene, mixed isomers 1330-20-7

SARA 313

This product contains a chemical or chemicals which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA 313).

- 98-82-8 cumene 1.3 %
- 111-76-2 ethylene glycol monobutyl ether 2.3 %
- 100-41-4 ethyl benzene 3.5 %
- 95-63-6 1,2,4-trimethylbenzene 7.8 %
- 1330-20-7 xylene, mixed isomers 20.0 %

TSCA

All chemicals in this product are listed, or are exempt from listing, on the TSCA inventory unless they are listed here:

SECTION 16 - OTHER INFORMATION

Hazardous Material Information System (HMIS)

| | | |
|----------------------------|--------------------------------|---|
| HEALTH | <input type="text" value="2"/> | HMIS & NFPA Hazard Rating Legend * = Chronic Health Hazard 0 = INSIGNIFICANT 1 = SLIGHT 2 = MODERATE 3 = HIGH |
| FLAMMABILITY | <input type="text" value="3"/> | |
| PHYSICAL HAZARD | <input type="text" value="0"/> | |
| PERSONAL PROTECTION | <input type="text"/> | |

DISCLAIMER: The information provided in this MSDS has been obtained from sources believed to be accurate and reliable. It is furnished without warranty of any kind, express or implied. Recipients should determine that the information is current and suitable for the protection of the environment and the health and safety of your employees and users of this product.

Date revised: 2015-11-20
Date Prepared: 3/30/2016

Reviewer Revision 1