Mobile Paint Mfg. Co., Inc.

SAFETY DATA SHEET

OSHA HCS (29 CFR 1910-1200)

SECTION 1 - PRODUCT AND MANUFACTURER IDENTIFICATION

Product Name: PRIMER REDUCER - MAK Product Code: 9000-906

Mobile Paint Mfg. Co., Inc. P.O. Box 717 4775 Hamilton Blvd. Theodore, AL 36582

Emergency Phone: Chemtel, Inc 1-800-255-3924 +1-813-248-0585 (Chemtel 24 Hour Emergency Number)

Information Phone: 251-443-6110 FAX: 251-408-0410

Product Use: Paint reducer Not recommended for: Contact Manufacturer

SECTION 2 - HAZARD DATA

GHS Ratings:

ono Ratings.			
Flammable liquid Oral Toxicity Inhalation Toxicity	3 Acute Tox. 4 Acute Tox. 4	Flash point >= 23°C and <= 60°C (140°F) Oral>300+<=2000mg/kg Gases>2500+<=20000ppm, Vapors>10+<=20mg/l, Dusts&mists>1+<=5mg/l	
GHS Hazards			
H226 H302 H332 <u>GHS Precautions</u>	Flammable liquid ar Harmful if swallowed Harmful if inhaled		
P210	Keep away from hea	at/sparks/open flames/hot surfaces – No smoking	
P233	Keep container tightly closed		
P240	Ground/bond container and receiving equipment		
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment		
P242	Use only non-sparking tools		
P243	Take precautionary measures against static discharge		
P261	Avoid breathing dust/fume/gas/mist/vapours/spray		
P264	Wash hands and skin thoroughly after handling		
P270	Do not eat, drink or smoke when using this product		
P271	Use only outdoors or in a well-ventilated area		
P280	Wear protective gloves/protective clothing/eye protection/face protection		
P312	Call a POISON CENTER or doctor/physician if you feel unwell		
P330	Rinse mouth		
P301+P312		call a POISON CENTER or doctor/physician if you feel unwell	
P303+P361+P353	IF ON SKIN (or hair Rinse skin with wate): Remove/Take off immediately all contaminated clothing. er/shower	
P304+P340	IF INHALED: Remo for breathing	ve victim to fresh air and keep at rest in a position comfortable	
P370+P378	0	dry sand, dry chemical or alcohol-resistant foam for extinction	
P403+P235		lated place. Keep cool	
P501		/container in accordance with all local, regional, national and	



SECTION 3 - COMPOSITION / HAZARDOUS INGREDIENTS			
Chemical Name	CAS number	Weight Concentration %	
methyl n-amyl ketone	110-43-0	90.00% - 100.00%	

SECTION 4 - FIRST AID MEASURES

Inhalation: Remove to fresh air. Administer oxygen if breathing is difficult. Restore breathing if necessary and call a physian immediately. Treat symptomatically.

Eyes: Remove contact lenses if worn. Flush immediately with large amounts of water for at least 15 minutes. If symptoms persist, consult with a doctor for medical treatment.

Skin: Wash affected areas with soap and water. Remove and launder contaminated clothing. Consult a doctor if skin irritation continues.

Ingestion: Do not induce vomiting. Rinse out mouth and drink plenty of water to dilute. Never give anything by mouth to an unconcious person. Get medical help immediately.

Most important symptoms and effects, both acute and delayed

Symptoms: No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians: Treat symptomatically

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point: 38 C (100 F) LEL: 1.00

UEL: 8.00

Extinguishing media

Suitable extinguishing agents:

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. CO2, extinguishing powder or water spray may be effective.

For safety reasons unsuitable extinguishing agents: CAUTION! Use of water spray may be inefficient.

Unusual Fire and Explosion Hazards

Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers.

Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Advice for firefighters

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention. Keep containers tightly closed. Isolate from heat, sparks, and open flame.

Protective equipment:

Full protective quipment including self-contained breathing apparatus should be used.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol. Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation. Keep away from ignition sources. Protect from heat. **Environmental precautions:** Do not allow to enter sewers/ surface or ground water. See Section 12 for additional ecological information.

Methods and material for containment and cleaning up:

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders). Dispose contaminated material as waste according to item 13. Do not flush with water or aqueous cleansing agents. Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7 - HANDLING AND STORAGE

Handling Precautions:

Precautions for safe handling

Prevent formation of fine mist and vapor buildup during and after use. Avoid splashes or spray in enclosed areas. Use only in well ventilated areas. Do not get in eyes. Avoid skin contact. Can cause allergic respiratory reaction. Can cause allergic skin reaction. Prevent prolonged or repeated breathing of vapors or spray mist. Avoid breathing of sanding dust. Wash contaminated clothing thoroughly. Wash skin thoroughly with soap and water after handling. Close container after each use. Do not transfer this product to unlabeled containers. Do not handle until the manufacturer's safety precautions have been read and understood. Keep out of reach of children.

Information about protection against explosions and fires:

Keep ignition sources away. Do not smoke. Protect against electrostatic discharges.

Storage Requirements:

Do not store above 120 F. Store large quantities only in buildings designed to comply with OSHA 1910.106. Keep closures tight and container upright to prevent leakage. Do not store or use near heat, sparks or flame. Never use pressure to empty. Drum must not be washed out or used for other purposes. Drums of this material should be grounded when pouring.

Regulatory Requirements:

Consult NFPA Code. Use approved bonding and grounding procedures.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION				
Chemical Name / CAS No. OSHA Exposure Limits		ACGIH Exposure Limits	Other Exposure Limits	
methyl n-amyl ketone 110-43-0	Z1 TWA 100ppm/465mg/m3 PO TWA 100ppm/465mg/m3	TWA 50 ppm	NIOSH REL TWA 100ppm/465mg/m3	

Engineering Controls:

Appropriate engineering controls include ventilations systems, eyewash stations and emergency showers.

Ventilation:

All application areas should be ventilated in accordance to OSHA regulation 29 CFR 1910.94, 1910.107, 1910.108. Remove decomposition products formed during welding or flame cutting on surface coated with this product. If baking, vent fumes.

Work / Hygenic Practices:

Wash skin thoroughly before breaks and meals and at the end of work period .

Respiratory Protection:

Use a NIOSH-approved respirator to prevent overexposure, when exposure exceeds occupational exposure limits (Section 8). Use either an atmosphere-supplying respirator or an air-purifying respirator for organic vapors in compliance with 29 CFR 1910.134, with provision for mist removal if conditions so indicate. If isocyanate compounds are present in spray applications or other situations which may produce inhalation exposures, use a respirator that is

recommended or approved for use in isocyanate-containing environments.

Eye Protection:

Safety eyewear including splashguards or side shields recommended.

Protective Gloves:

Recommended. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material should be based on consideration of the penetration times, rates of diffusion and the degradation.

Other Protective Clothing or Equipment:

Use protective outerwear and prevent prolonged skin contact with contaminated clothing.

Contaminated Equipment:

Thoroughly clean all contaminated clothing and personal protection equipment.

SECTION 9 - PHYSICAL / CHEMICAL CHARACTERISTICS

Information on basic physical and chemical properties

Appearance: Liquid Vapor Pressure: 2.8 mbar @ 20 C Vapor Density: 3.9 Specific Gravity: 0.82 Freezing point: No information available Boiling range: N/A Evaporation rate: slower than ether Partition coefficient (n- no data octanol/water): Decomposition temperature: No information available VOC - water/exempt (g/L) 816 VOC emitted (g/L) 816 Odor: Typical solvent odor Odor threshold: No information available pH: No information available Melting point: No information available Solubility: No information available Flash point: 100 F,38 C Flammability: No information available Autoignition temperature: N/A Viscosity: No information available VOC - water/exempt (Ib/gal) 6.80 VOC emitted (Ib/gal) 6.80

SECTION 10 - STABILITY AND REACTIVITY

Reactivity - No data available

Chemical stability - Stable under recommended storage conditions.

STABLE

Possibility of Hazardous Reactions - None under normal conditions of use.

Conditions to Avoid - Heat, sparks, open flame, static electricity, sources of ignition, elevated temperatures .

Incompatible Materials - Strong acids and alkali, strong oxidizing agents.

Incompatibility of Individual Components:

No information available

Hazardous decomposition products - Carbon monoxide and carbon dioxide Information for Individual Components:

methyl n-amyl ketone

No information available

Hazardous polymerization will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Mixture Toxicity

Oral Toxicity LD50: 1,670mg/kg Dermal Toxicity LD50: 2,001mg/kg Inhalation Toxicity LC50: 17mg/L

Component Toxicity

110-43-0

Oral LD50: 1,670 mg/kg (rat) Dermal LD50: 2,001 mg/kg (rat) Inhalation LC50: 17 mg/L (rat)

CHRONIC HEALTH HAZARDS:

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system

damage. Routes of Entry:					
Inhalation	Skin Contact	Eye Contact	Ingestion		
Target Organs: No information a	available	-			
Effects of Overexpos	sure				
Eye contact:	•	et can cause severe ir n some individuals.	rritation, redness, tearing, blurred vision. May be a		
Skin contact:	Skin contae some indiv		te iritation, defatting, dermatitis. May be a sensitizer in		
Inhalation:	nervous sy	Anesthetic, excessive inhalation can cause irritation of the respiratory tract, or acute nervous system depression characterized by headache, dizziness, staggering gait, confusion, unconsciousness, coma and even asphyxiation.			
Ingestion:	Aspiration	Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury and possibly even death.			
Sensitization:	No data av	ailable.			
Mutagenicity:	No data av	ailable.			
Reproductive Toxicity:	No data av	ailable.			
Teratogenicity:	No data av	ailable.			
Specific Target Organ Toxicity - Single Exposure:	No data av	ailable.			
Specific Target Organ Toxicity - Repeated Exposu	No data av 'e:	ailable.			
.					

Carcinogenicity:

For Mixture - No information available

For Components - The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

None			
None	-	No information available	
CAS Number	Description	% Weight Carcinogen Rating	

Persistence and degradability - No information available.

Bioaccumulative potential - No information available.

Mobility in soil - No information available.

Ecotoxical effects - No information available.

Other adverse effects - No information available.

Additional ecological information:

General notes:

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

Component Ecotoxicity

LC50 Pimephales promelas (fathead minnow): 131 mg/l @ 96h; EC50 Daphnia magna (water flea): >100 mg/l @ 48h; EC50 Selenastrum capricornutum (green algae): 98.2 mg/l @ 72h

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste disposal methods:

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Residual materials should be treated as hazardous unless proven to be otherwise.

Notice to user:

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

Empty Container Warning:

Emptied containers may contain product residue. Follow label warnings even after container is emptied. Residual vapors may explode on ignition. Do not reuse container.

SECTION 14 - TRANSPORT INFORMATION

Shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transportation does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment and compliance with applicable regulations is the sole responsibility of the person offering the product for transport.

Agency	Proper Shipping Name	UN Number	Packing Group	Hazard Class
DOT	Paint Related Material, Thinner	1263	II	3

SECTION 15 - REGULATORY INFORMATION

California Proposition 65

This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

- None

CERCLA

This material, as supplied, contains the following chemicals regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) - 40 CFR 302

- None

Hazardous Air Pollutants (HAPs) Content

Hazardous Air Pollutants subject to the provisions of the Clean Air Act, Title I Section 112 'National Emission Standards for Hazardous Air Pollutants'

- None

Massachusetts RTK:

methyl n-amyl ketone 110-43-0

New Jersey RTK:

methyl n-amyl ketone 110-43-0

Pennsylvania RTK:

methyl n-amyl ketone 110-43-0

Rhode Island Hazardous Substance List:

- None

SARA 313

This product contains a chemical or chemicals which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA 313).

TSCA

All chemicals in this product are listed, or are exempt from listing, on the TSCA inventory unless they are listed here:

SECTION 16 - OTHER INFORMATION

Hazardous Material Information System (HMIS)



DISCLAIMER: The information provided in this MSDS has been obtained from sources believed to be accurate and reliable. It is furnished without warranty of any kind, express or implied. Recipients should determine that the information is current and suitable for the protection of the environment and the health and safety of your employees and users of this product.

Date revised: 2015-09-29 Date Prepared: 9/29/2015 **Reviewer Revision 1**